



SPATECH D-DC SERIES ULTRASONIC CLEANERS

SPATECH D-DC ultrasonic series, our featured product, a selection of D and DC (heavy-duty) series of ultrasonic bench-top cleaners with different tank size, output power, output frequency to match your cleaning needs. Special attention has been paid to its effectiveness, technical features, user friendliness and design.

These models are ideally suited for washing small industrial parts, as well as for commercial /consumer uses. Applications include, but are not limited to: jewelry, optical parts, small gears, machined parts, bearings, carburetor components and surgical instruments. All Systems Include:


- ❑ Stainless steel tank construction
- ❑ Stainless steel basket
- ❑ Adjustable timer for ultrasonic control
- ❑ 240V AC standard
- ❑ 110 or 115V AC available
- ❑ Adjustable, thermostatically controlled heat (for models with heater)



Digital Control Panel



Drainage



Stainless Steel Basket

SPATECH D-DC SERIES ULTRASONIC CLEANERS

TABLE 1.

Technical Specification	D80 / D80H	D150 / D150H	D200 / D200H	DC80 / DC80H	DC150 / DC150H	DC200 / DC200H DC300 / DC300H	DC400 / DC400H DC600 / DC600H
Tank Dimension LxWxH (mm)	150/135/100	295/150/100	300/240/150	150/135/100	300/160/150	300/240/150	500/300/200
Ex. Tank Dimension LxWxH (mm)	175/160/200	320/175/200	330/285/270	175/160/280	330/205/330	330/285/330	530/345/380
Capacity of Container (Liter)	2	4.5	10.8	2	7.2	10.8	30
Tank Material	SUS 304#1.0t	SUS 304#1.0t	SUS 304#1.5t	SUS 304#1.0t	SUS 304#1.0t	SUS 304#1.5t	SUS 304#1.5t
Tank Cover	YES	YES	YES	YES	YES	YES	YES
Drain	NO	NO	YES	NO	YES	YES	YES
Output Frequency (kHz)	43	43	43	40	40	40	40
Output Power (w)	80	150	200	80	150	200 / 300	400 / 600
Timer Setting (minute)	10 / 30	99	99	10 / 30	99	99	99
Heater	NIL / 40	NIL / 115	NIL / 230	NIL / 60	NIL / 115	NIL / 230	NIL / 500
Power Supply	AC 100 ~ 120V / AC 220 ~ 240V				50 / 60Hz		
Net Weight (kg)	2	3.3	8	2.5	8	10	17.5

Typical Applications of an Ultrasonic Cleaner

- Bio-Tech Division
- Bio-Medical Division
- R & D Division
- Lab Test Division
- Hospital (CSSD) Division
- Semiconductor (SMT)
- Optical & Photoelectricity Division
- Electronic Component Division
- Jewelry, Pewter, Watch & Film Coating
- Printer Manufacture & Service Division
- PCB Manufacture & Assemblies
- Plastic Division
- Precision Machinery Division
- Precision Hardware Division
- Plating & Chemical Fiber Division



Technical Specification	DC600H (ED)
Tank Dimension LxWxH (mm)	500/300/300
Ex. Tank Dimension LxWxH (mm)	530/345/480
Capacity of Container (Liter)	45
Tank Material	SUS 304#1.5t
Tank Cover	YES
Drain	YES
Output Frequency (kHz)	40
Output Power (w)	600
Timer Setting (minute)	99
Heater	1000
Power Supply	refer table 1
Net Weight (kg)	22

For More Information

For more information about SPATECH, visit our website www.spatechindustries.com



SPATECH INDUSTRIES (M) SDN BHD (726402-K)
49G, Jalan Anggerik Vanilla T31/T, Sec 31, Kota Kemuning,
40460 Shah Alam, Selangor Darul Ehsal, Malaysia.

Tel: +6 03-5121 5329
Fax: +6 03-5122 7094
info@spatechindustries.com